

## Shandong Volford Machinery Co,. Ltd Shandong Volford Tractors Co., Ltd





Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2, 8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more agronomy work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	,	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

### [25-70hp]

## VF454



#### **Tractors VF454 Features**

01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more agronomy work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
РТО	r/min	540/760/1000

[25-70hp]
VF504



01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more agronomy work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
РТО	r/min	540/760/1000

## [25-70hp]

**VF504** 



#### Tractors VF504 Features

01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more agronomy work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000





Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more agronomy work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

[ 25-70hp ]

## VF504



**Tractors VF504 Features** 

01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



#### **Tractors VF704 Features**

#### 01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	/	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

## [ 25-70hp ]

# VF704



#### **Tractors VF704 Features**

01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

03 High Performance Clutch

Double-acting clutch for more farming work requirements.

04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

## [ 25-70hp ]



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000





Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+2,8+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	25-70
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3200/3500*1530/1580*2020/2100
Wheelbase	mm	1780、1800、1840
Front/Rear track	mm	Front track 960-1300 Rear track 960-1300
Min fround clearance	mm	380/ 320
Min operational Weight	kg	1721-2047
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	8+2,8+8
Tire	1	Front 6.00-16/6.50-16 6.50-16/7.5-16/7.5-20 Rear 8.3-24/9.50-24/11.2-24/11.2-28/12.4-24/12.4-28
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

### [ 50-110hp ]

## **VF804**



#### **Tractors VF804 Features**

01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+4、12+12 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3235-4301
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	,	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
РТО	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

O2 High Performance Chassis

Bold And Heavier,8+4, 12+12 shift high efficient quick swith.

03 High Performance Clutch

Double-acting clutch for more farming work requirements.

04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3020-4001
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	,	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



02 High Performance Chassis

Low Fuel Consumption Easy Maintenance.

Bold And Heavier,8+4, 12+12 shift high efficient quick swith.

03 High Performance Clutch

Double-acting clutch for more farming work requirements.

04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3020-4001
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	1	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000

## [ 50-110hp ]



#### 01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+4, 12+12 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3235-4301
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	1	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier, 12+12, 8+4 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3235-4301
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	1	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier,8+4、12+12 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	50-110
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	3910/3940/4060*1740/1880*2600/2755/2800
Wheelbase	mm	2040
Front/Rear track	mm	Front track 1250-1550 Rear track 1300-1500
Min fround clearance	mm	310-400
Min operational Weight	kg	3235-4301
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	12+12、8+4
Tire	/	Front 8.3-20、8.3-24、9.5-24 Rear 12.4-28、11-32、14.9-28、14.9-30
Suspension Type	1	Rear, Three-point, Cat I
РТО	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier, 16+8 shift high efficient quick swith.

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Power	hp	100-150
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	4750*2230*3050
Wheelbase	mm	2300
Front/Rear track	mm	Front 1750 Rear 1740
Min fround clearance	mm	460
Min operational Weight	kg	4475
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	16+8
Tire	1	Front 14.9-26
		Rear 18.4-38
Suspension Type	1	Rear, Three-point
PTO	r/min	540/760/1000



Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier, 16+16 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Power	hp	180-240
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	5500*2480*3080
Wheelbase	mm	2820
Front/Rear track	mm	Front track 1970 Rear track 1700
Min operational Weight	kg	7785
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	16+16
Tire	1	Front 16.9-28
		Rear 20.8-38
Suspension Type	1	Rear, Three-point
PTO	r/min	540/760/1000

### [ 200-240hp ]





01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

02 High Performance Chassis

Bold And Heavier, 16+16 shift high efficient quick swith .

03 High Performance Clutch

Double-acting clutch for more farming work requirements.

04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Power	hp	200-240
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	5350*2350*3200
Wheelbase	mm	2780
Front/Rear track	mm	Front track 1900 Rear track 1700-2300
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	16+16
Tire	1	Front 16.9-30 16.9-28 504/65R30 Rear 20.8-42 20.8-38 18.4-42 650/65R42
Suspension Type	1	Rear, Three-point
PTO	r/min	540/760/1000

[ 240-280hp ]



#### 01 Strong Power Engine

Low Fuel Consumption Easy Maintenance.

#### 02 High Performance Chassis

Bold And Heavier, 16+16 shift high efficient quick swith .

#### 03 High Performance Clutch

Double-acting clutch for more farming work requirements.

#### 04 Compatible With Various Farm Implements

Equipped with three-point suspension, multi-way valve, strong lift and down device.

Item	Unit	Data
Power	hp	240-280
Туре	1	Basic model, roll bar, canopy, cab
Color	1	Red, Blue, Green, Yellow, Others
Overall Dimensions	mm	5520*2560*3220
Wheelbase	mm	2845
Front/Rear track	mm	Front track 1810-2070 Rear track 1820-2370
Min fround clearance	mm	530
Min operational Weight	kg	7325
Engine type	1	In-line, Water-cooled, Four-stroke, Direct injection
Gearbox Type	1	16+16
Tire	1	600/70R30 / 710/70R42
Suspension Type	1	Rear, Three-point, Cat 3
PTO	r/min	540/760/1000